


2016 AASHTO Wind Map



Notes

- Values are 3-second gust speeds in m/s (mph) at 10 m (32.8 ft) above ground for Exposure C category and are associated with an annual probability of 0.02 (50-year mean recurrence interval)
- The wind map is intended as a general guide. Always consult local authorities to determine maximum wind velocities, gusts, and special conditions for your installation.
- Hawaii has a 105 mph wind velocity.
- Puerto Rico has a 125 mph wind velocity.
- Caution must be taken when selecting wind velocity in special wind regions as indicated in the map above. These areas include:
 - Open land, oceans, or large bodies of water
 - Mountainous regions and gorges
 - Areas where extreme wind conditions such as hurricanes and tornadoes are common.
- The effective projected area (EPA) of the sum of all fixtures and arms must not exceed the maximum allowable pole EPA for the selected design wind speed.
- It is the responsibility of the specifier to correctly select a pole for a given wind load per the AASHTO standards.
- Pole foundations should be designed per the soil conditions and local codes. Structura does not offer foundation design recommendations.
- Consult the factory for luminaire arms greater than 24" in length and luminaires greater than 50 lbs.

maximum wind loading

STRUCTURA

Duo

Standard

		Allowable Pole EPA							
Fixture Height (ft)	Wall Thickness (in)	90mph	100mph	110mph	120mph	130mph	140mph	150mph	
12'	0.125"	8.44	6.46	4.99	3.87	3.00	2.31	1.76	
12'	0.250"	11.63	9.04	7.12	5.67	4.53	3.63	2.91	
16'	0.125"	5.06	3.59	2.50	1.68	1.03	-	-	
16'	0.250"	7.42	5.50	4.08	3.01	2.17	1.50	-	
20'	0.125"	2.56	1.44	-	-	-	-	-	
20'	0.250"	4.36	2.90	1.82	1.00	-	-	-	

XL

		Allowable Pole EPA							
Fixture Height (ft)	Wall Thickness (in)	90mph	100mph	110mph	120mph	130mph	140mph	150mph	
20'	0.250"	22.82	17.28	15.71	12.19	9.45	7.28	5.52	
22'	0.250"	18.93	14.01	12.63	9.50	7.07	5.14	3.59	
24'	0.250"	15.61	11.21	9.97	7.18	5.00	3.28	1.88	
26'	0.250"	12.72	8.76	7.65	5.13	3.17	1.61	-	
28'	0.250"	10.18	6.60	5.58	3.31	1.52	-	-	
30'	0.250"	7.92	4.65	3.73	1.65	-	-	-	

Tenon Top

		Allowable Pole EPA							
Pole Height (ft)	Wall Thickness (in)	90mph	100mph	110mph	120mph	130mph	140mph	150mph	
12'	0.125"	8.44	6.46	4.99	3.87	3.00	2.31	1.76	
12'	0.250"	11.63	9.04	7.12	5.67	4.53	3.63	2.91	
14'	0.125"	6.61	4.91	3.66	2.70	1.95	1.36	-	
14'	0.250"	9.35	7.13	5.49	4.24	3.27	2.50	1.87	
16'	0.125"	5.06	3.59	2.50	1.68	1.03	-	-	
16'	0.250"	7.42	5.50	4.08	3.01	2.17	1.50	-	
18'	0.125"	3.70	2.42	1.48	-	-	-	-	
18'	0.250"	5.75	4.08	2.85	1.92	1.19	-	-	